



# ***ManciniTende***

**PRODUCT CATALOGUE**

**MANCINI TENDE S.r.l.**

Via G. Di Vittorio, 20 48026 Russi (RA) - ITALY

T: (+39) 0544-582445 - F: (+39) 0544-586658

✉ [mancini@mancinitende.com](mailto:mancini@mancinitende.com)

🌐 [www.mancinitende.com](http://www.mancinitende.com)

f [www.facebook.com/mancinitende](http://www.facebook.com/mancinitende)



# Basic



Ideal for medium to large covers / recommended max size length 8-14 m X width 6-8 m

## Features and accessories

Ideal for special applications and sport teams.

- > Adjustable tent, double-ply or single-ply
- > Galvanized iron frame or lighter and sturdier stainless steel frame (optional)
- > Safety valve set and hose burst valve
- > Roof rack with rounded edges, if envisaged
- > Emergency manual pump
- > Emergency remote control

### Optional functions

- > Automated central poles (single-ply cover only)
- > Forward-backward positioning
- > Lateral positioning
- > Foldable front and rear attachments
- > Structure moving to the vehicle side
- > Tailor-made built-in version on vending vehicles

## Technical specifications

- > Standard box height: 25 cm
- > Total height from roof: 28-30 cm, depending on the vehicle
- > Average total weight: 460 kg (galvanized iron), 520 kg if fitted with positioning system
- > Average total weight: 400 kg (stainless steel), 480 kg if fitted with positioning system

# Europlus



Ideal for small-medium dimensions / recommended max size length 5-8 m X width 4-6 m

## Features and accessories

- > Adjustable tent, double-ply or single-ply
- > Galvanized iron frame or lighter and sturdier stainless steel frame (optional)
- > Partial safety valve set
- > Roof rack with rounded edges, if envisaged
- > Emergency manual pump
- > Emergency remote control

### Optional functions

- > Automated central poles (single-ply cover only)
- > Forward-backward positioning
- > Lateral positioning
- > Structure moving to the vehicle side (*Agility* model);
- > Upon request, low awnings with the bottom at 18 cm from the vehicle roof

## Technical specifications

- > Standard box height: 22 cm
- > Total height from roof: 26-28 cm, depending on the vehicle
- > Average total weight: 320 kg (galvanized iron), 370 kg if fitted with positioning system
- > Average total weight: 280 kg (stainless steel), 330 kg if fitted with positioning system

# New Evolution - *Size adjustable*



Ideal for vending

spaces of medium dimensions, recommended max size: length 5-10 m X width 4-6 m

## Features and accessories

- > Adjustable tent, double-ply cover
- > **Size can be reduced by 1,5 m to 3 m**, on one or two sides; the size adjusting function allows to adjust the overall dimensions, to suit different parking spaces, thus making opening and closing easier
  - > Galvanized iron frame or lighter and sturdier stainless steel frame (optional)
  - > Safety valve set and hose burst valve
  - > Roof rack with rounded edges, if envisaged
- > Emergency manual pump
- > Emergency remote control

### Optional functions

- > Forward-backward positioning
- > Lateral positioning
- > Manual foldable front and rear attachments

## Technical specifications

*> Size can be reduced by 1,5 m to 3 m on one or two sides*

- > Standard box height: 25 cm
- > Total height from roof: 28-30 cm, depending on the vehicle
- > Average total weight: 540 kg (galvanized iron), 600 kg if fitted with positioning system
- > Average total weight: 480 kg (stainless steel), 530 kg if fitted with positioning system

# Liberty - Size adjustable



**Brand New Model with Patent.** Ideal for medium to large covers.

Size can be reduced by 1.0 to 2.0 m on 1 or 2 sides; forward/backward positioning system

## Features and accessories

Is a versatile tent with a innovative frame that makes the tent compact and flexible. The frame is made of a carriage that allows to reduce and slide the tent; the size adjusting function allows to adjust the overall dimensions, to suit different parking spaces.

- > Adjustable tent, double-ply cover
- > Size can be reduced by 1 m to 2 m, on one or two sides
- > Stainless steel frame, lighter and sturdier

- > Safety valve set and hose burst valve
- > Roof rack with rounded edges, if envisaged
- > Emergency manual pump
- > Emergency remote control

### Optional functions

- > 1 m forward-backward positioning
- > Lateral positioning
- > Automated foldable front and rear attachments

### Technical specifications - **Liberty Europlus**

*Ideal for small-medium covers, recommended max size:*

*length 5-9 m X width 4-6 m*

- > Standard box height: 25 cm
- > Total height from roof: 32-35 cm, depending on the vehicle
- > Average total weight: 500 kg (stainless steel)

### Technical specifications - **Liberty Basic**

*Ideal for medium to large covers, recommended max size:*

*length 8-14 m X width 6-8 m*

- > Standard box height: 25 cm
- > Total height from roof: 35-38 cm, depending on the vehicle
- > Average total weight: 560 kg (stainless steel)



**ManciniTende**

**PROFESSIONALISM  
KNOW-HOW  
EXPERTISE**

Mancini Tende has been working in the industry for 20 years, providing a wide range of awnings for vending vehicles, from semi-automatic to fully automated awnings operated by remote control. The Awnings provide shade and rain protection and make your workspace more comfortable.



takes  
40''  
to open



**RELIABILITY  
AND  
HIGH  
QUALITY**

**Find all information and news  
on our website and social networks**



**[www.mancinitende.com](http://www.mancinitende.com)**



**REQUEST**  
**A QUOTE**  
**TO OUR**  
**DEALER**

**For more information, assistance service, installation  
contact:**